



KEY FEATURES

- Small Compact Hybrid Communication Solution; the IP and Digital World in One Box
- Built-in Unified Messaging: Voicemail, Call Center, Simplified Maintenance and More
- Supports an Extensive Lineup of Phones that Includes SIP/IP/Digital and DECT Portables
- Pre-installed Cards and Activation Keys for Small Installations with Option to Unlock
- Robust Standard Two-year Warranty

THE PANASONIC KX-NS700G SMALL COMPACT HYBRID COMMUNICATION PLATFORM

The KX-NS700G harnesses the power of an IP communications platform while retaining the ability to maintain a legacy PBX digital platform. It is a cost-saving system that is ideal for small businesses which can be flexibly configured with both digital and IP configurations.

The KX-NS700G has intelligent features like built-in voicemail, call center monitoring and reporting, as well as access to our standard Communication Assistant application tool. You can also try advanced features before purchasing, like two-way recording, message storage backup, voicemail-to-email notification, mobility and advanced Communication Assistant.

KX-NS700G

DHLC4

EXTN

SYSTEM CAPACITY

TYPE	Without KX-NSF999W AK		With KX-NSF999W AK***			
	PRE-INSTALLED KX-NS700G	MAXIMUM KX-NS700G	KX-NS700G STAND-ALONE MAXIMUM	KX-NS700G +1 KX-NS720 MAXIMUM	KX-NS720 + 2 KX-NS720 MAXIMUM	KX-NS720 + 3 KX-NS720 MAXIMUM
Trunk (ch)	6	102	102	138	174	210
Legacy	6	38 (30+8)	38 (30+8)	74	110	146
LCOT	6	12	12	24	36	48
PRI23	0	23	23	46	69	92
T1	-	-	-	-	-	-
IP	0	64	64	64		
SIP	0	64	64	64		
H323	0	32	32	32		
Extensions (ch) (DXDP)	22 (22)	26 (26)	166 (168)	198 (208)	230 (248)	262 (288)
Legacy (DXDP)	22 (22)	22 (22)	38 (40)	70 (80)	102 (120)	134 (160)
SLT	4	4	36 (32+4)	68 (64+4)	100 (96+4)	132 (128+4)
DPT (DXDP)	18 (18)	18 (18)	34 (32+2) (38)	66 (64+2) (78)	98 (96+2) (118)	130 (128+2) (158)
APT	0	0	8	16	24	32
IP	0 (4 IP-PT AK)	4	128**			
IP-PT	0 (4 IP-PT AK)	4	128			
SIP	0 (4 IP-PT AK)	4	128			
P-SIP*	0 (4 IP-PT AK)	4	128			
SIP Phone	0	0	128			
KX-UT series	0 (4 IP-PT AK)	4	128			
CS (pcs)	0	24	24	32	40	48
DPT-CS(2ch)	0	8	8	16	24	32
DPT-CS(8ch)	0	4	4	8	12	16
IP-CS(8ch)	0	16	16	16	16	16
New IP-CS(4ch/8ch)	0	32	32	32	32	32
SIP-CS	0	16	16	16	16	16
PS (DECT) (pcs)	128	128	128			
VM						
ESVM (ch)	2	2	2			
Built-in UM (ch)	2	24	24			
TVA Unit	2	2	2			
Door phone	0	2	2	4	6	8
Door phone	0	2	2	4	6	8
Door opener	0	2	2	4	6	8
Sensor	0	2	2	4	6	8
Power Failure Transfer Post	2	2	2	2	2	2
Music On Hold or External Pager	(2)	2	2	2	2	2
MDH/BGM	(2)	2	2	2	2	2
EPS	(2)	2	2	2	2	2

KX-HDV series, KX-NIV series, KX-TGP600. **When IP extensions over 32 are required or KX-NS720, Expansion Capacity AK (KX-NSF911W) is required. ***Except One Look Networking.

OPTIONS: HARDWARE

	COMPONENT	MODEL NO.	INSTALLED IN
DSP	S (63 resources)*	KX-NS5110	DSP Card Slot
	M (127 resources)**	KX-NS5111	
	L (254 resources)**	KX-NS5112	
Storage Memory ¹	XS (VM Recording Time: 40 hours)*	KX-NS7134	Storage Memory Card Slot
	S (VM Recording Time: 200 hours)**	KX-NS7135	
	M (VM Recording Time: 400 hours)**	KX-NS7136	
Trunk	LCOT6*	KX-NS5180	Trunk/Doorphone Slot
	PRI23	KX-NS5290	
Extension	DPH2	KX-NS5162	Extension Slot
	DHLC4**	KX-NS5170	
	DLC8**	KX-NS5171	
	DLC16*	KX-NS5172	
	MCSLC8**	KX-NS5173	
	MCSLC16**	KX-NS5174	
	EXP-M**	KX-NS7130	
Expansion Master Card	EXP-M**	KX-NS7130	EXP-M Slot
Remote Modem	RMT	KX-TDA0196	RMT Slot

* Pre-installed with KX-NS700G. ** Requires KX-NSF999 to operate.

SOFTWARE ACTIVATION KEYS

COMPONENT	MODEL NO.	MAXIMUM
Networking	KX-NSN002	1 activation key
System Function	Call Center Feature	ACD Report ² , Announcement of waiting number for queuing
	Expansion Capacity**	KX-NSF991
IP Trunk	2 ch	KX-NSM102
	4 ch	KX-NSM104
	8 ch	KX-NSM108
	16 ch	KX-NSM116
	1 ch	KX-NSM201
IP Telephone ² - User License	5 ch	KX-NSM205
	10 ch	KX-NSM210
	20 ch	KX-NSM220
	Up to 4 ch	Preinstalled
	1 ch	KX-NSM501
	5 ch	KX-NSM505
	10 ch	KX-NSM510
	20 ch	KX-NSM520
	1 ch	KX-NSM701
	5 ch	KX-NSM705
Cellular Phone Extension - User License	10 ch	KX-NSM710
	20 ch	KX-NSM720
	1 ch	KX-NSE101
	5 ch	KX-NSE105
Mobile Extension	10 ch	KX-NSE110
	20 ch	KX-NSE120

* Pre-installed with KX-NS700G. ** Requires KX-NSF999 to operate.

SOFTWARE ACTIVATION KEYS (cont.)

COMPONENT	MODEL NO.	MAXIMUM	
Unified Messaging System	Feature		
	Two-way REC [Recording] Control	KX-NSU002	1 activation key
	Message Backup	KX-NSU003	1 activation key
	Unified Messaging Channel	2 ch	Preinstalled
		2 ch	KX-NSU102
		4 ch	KX-NSU104
	User [Mailbox] License		
	Email (IMAP4) Client/IP-CS Channel	1 user	KX-NSU201
		5 users	KX-NSU205
		10 users	KX-NSU210
20 users		KX-NSU220	
Two-way Recording/Two-way Transfer	All users	KX-NSU299	
	1 user	KX-NSU301	
	5 users	KX-NSU305	
	10 users	KX-NSU310	
	20 users	KX-NSU320	
All users	KX-NSU399		
User License			
CA Basic-Express	All users	Preinstalled	
	1 user	KX-NSA201	
	5 users	KX-NSA205	
	10 users	KX-NSA210	
	40 users	KX-NSA240	
128 users	KX-NSA249		
CA PRO	1 user	KX-NSA301	
CA Supervisor	1 user	KX-NSA401	
CA Operator Console	1 user	KX-NSA901	
CA Network Plug-in	5 users	KX-NSA905	
	10 users	KX-NSA910	
	40 users	KX-NSA940	
	128 users	KX-NSA949	
CA Thin Client	Thin Client Server Connection	KX-NSA010	
CSTA Multiplexer	Multiple CSTA Connection	KX-NSA020	
CTI License			
3rd Party CTI link	CTI interface	KX-NSF101	
Partner License			
Application Solutions	Pollys CCAccounting	KX-P-CC-ACCNT	
	Pollys CCAccounting A.L. ⁵	1-Year Included	
	Pollys CCAgent External CRM	KX-P-PYCCACRM	
	Pollys CCAgent External CRM	1-Year Included	
	Pollys CCView	KX-P-CCV1	
	Pollys CCView A.L. ⁵	1-Year Included	
	Pollys CCAccounting to CCView Upgrade	KX-P-ACCNTTOCCV	
	Pollys CCAccounting to CCView Upgrade A.L. ⁵	1-Year Included	
	Pollys CCRRecord SIP (4 ports)	KX-P-PYCCR-SIP-TA	
	Pollys CCRRecord SIP A.L. ⁵ (4 ports)	1-Year Included	
	Pollys CCRRecord LCO or SLT	4 users	KX-P-PCCRRISSET-4A
		8 users	KX-P-PCCRRISSET-8A
		12 users	KX-P-PCCRRISSET-12A
		16 users	KX-P-PCCRRISSET-16A
	Pollys CCRRecord Analog A.L.	24 users	KX-P-PCCRRISSET-24A
		4 users	1-Year Included
		8 users	1-Year Included
		12 users	1-Year Included
	Pollys CCRRecord Digital	16 users	1-Year Included
		24 users	1-Year Included
8 users		1-Year Included	
16 users		1-Year Included	
Pollys CCRRecord PRI	24 users	1-Year Included	
	1 port	KX-P-PCCRRIST-1	
	2 ports	KX-P-PCCRRIST-2	
	1 port	1-Year Included	
Pollys CCView Supervisor	2 ports	1-Year Included	
	Pollys CCView Supervisor	KX-P-PYCCV5	
	Pollys CCView Supervisor A.L. ⁵	1-Year Included	
	Pollys CCView CRM P-up	KX-P-PYCCACCV	
	Pollys CCView CRM P-up A.L. ⁵	1-Year Included	
	Pollys CCAgent	KX-P-PYCCACCV	
	Pollys CCAgent A.L. ⁵	1-Year Included	
	Pollys CCQueue Wait Time	KX-P-PYQUA	
	Pollys CCQueue Wait Time A.L.	1-Year Included	
	Pollys Dial Out Notification	KX-P-PYDOUTN	
	Pollys Dial Out Notification A.L.	1-Year Included	
	Pollys Outbound Dialer Pro	KX-P-PYSAOUT-P	
	Pollys Outbound Dialer Pro A.L.	1-Year Included	

¹Storage Memory for VM Time, ACD Report, SMDR Expansion

²An SD card is necessary to use ACD Reports

³IP Pts: KX-N1500/200 series IP proprietary phones

⁴IP Softphones: KX-TDA0350

⁵SIP Phones: KX-N1700 IP Conferencing Phone and third-party SIP phones (SIP hardphones/SIP softphones)

⁶The same number as the maximum number of allowable extensions

⁷Annual Maintenance License

Combined total for licenses: 350/system